

GM Optic Screen Sensor

Appearance



Detection Way	Model	Control Output	Detection Distance	Optic Axis Distance	Optic Axis Number	Detection Width	Min. Detectable Object
4cm Through-Beam	GM40-4N	N: NPN / P:PNP J: Relay Output	≤ 3m	40mm	4	120mm	φ50mm
	GM40-4J				6	200mm	
	GM40-6N				8	280mm	
	GM40-6J				10	360mm	
	GM40-8N				12	440mm	
	GM40-8J				16	600mm	
	GM40-10N				20	760mm	
	GM40-10J				24	920mm	
	GM40-12N						
	GM40-12J						
	GM40-16N						
	GM40-16J						
	GM40-20N						
	GM40-20J						
GM40-24N							
GM40-24J							
2cm Through-Beam	GM20-4N	N: NPN / P:PNP J: Relay Output	≤ 3m	20mm	4	60mm	φ30mm
	GM20-4J				6	100mm	
	GM20-6N				8	140mm	
	GM20-6J				10	180mm	
	GM20-8N				12	220mm	
	GM20-8J				16	300mm	
	GM20-10N				20	380mm	
	GM20-10J				24	460mm	
	GM20-12N						
	GM20-12J						
	GM20-16N						
	GM20-16J						
	GM20-20N						
	GM20-20J						
GM20-24N							
GM20-24J							