



INDUCTIVE PROXIMITY SWITCH				
Outward appearance code		LM14		
Appearance				
Dimension				
Flush	Detection distance		3mm	
	DC 6 ~ 36 V	NPN	NO	3003NA
			NC	3003NB
			NO+NC	3003NC
	V	PNP	NO	3003PA
			NC	3003PB
			NO+NC	3003PC
	two wire system		NO	3003LA
			NC	3003LB
	AC 90 ~ 250 V	SRC Control label silicon	NO	2003A
			NC	2003B
			NO+NC	
Relay output				
Non-flush	Detection distance		5mm	
	DC 6 ~ 36 V	NPN	NO	3005NA
			NC	3005NB
			NO+NC	3005NC
	V	PNP	NO	3005PA
			NC	3005PB
			NO+NC	3005PC
	two wire system		NO	3005LA
			NC	3005LB
	AC 90 ~ 250 V	SRC Control label silicon	NO	2005A
			NC	2005B
			NO+NC	
Relay output				
Control output	DC		200mA	
	SCR/Relay		300mA	
Output voltage dropDC/AC		DC<3V AC<10V		
Consumption current		DC<15mA AC<10mA		
Standard detected object		15×15×1(A3 iron)		
Repeated precision		0.02		
DC/AC Response frequency		300Hz/25Hz		
Working environment temperature		-25℃~75℃		
Insulation resistance		≥50MΩ		
Shell material		Metal		
Protection grade		IEC standard IP67		
Alternative model at home and abroad		LJ14A3-□□		