



INDUCTIVE PROXIMITY SWITCH				
Outward appearance code		LM18		
Appearance				
Dimension				
Flush	Detection distance		5mm	
	DC 6 ~ 36 V	NPN	NO	3005NA
			NC	3005NB
			NO+NC	3005NC
	PNP	NO	3005PA	
		NC	3005PB	
		NO+NC	3005PC	
	two wire system	NO	3005LA	
		NC	3005LB	
	AC 90 ~ 250 V	SRC Control label silicon	NO	2005A
			NC	2005B
			NO+NC	2005C
Relay output				
Non-flush	Detection distance		8mm	
	DC 6 ~ 36 V	NPN	NO	3008NA
			NC	3008NB
			NO+NC	3008NC
	PNP	NO	3008PA	
		NC	3008PB	
		NO+NC	3008PC	
	two wire system	NO	3008LA	
		NC	3008LB	
	AC 90 ~ 250 V	SRC Control label silicon	NO	2008A
			NC	2008B
			NO+NC	2008C
Relay output				
Control output	DC		200mA	
	SCR/Relay		300mA	
Output voltage dropDC/AC		DC<3V AC<10V		
Consumption current		DC<15mA AC<10mA		
Standard detected object		18×18×1(A3 iron)		
Repeated precision		0.02		
DC/AC Response frequency		200Hz/25Hz		
Working environment temperature		-25℃~75℃		
Insulation resistance		50MΩ		
Shell material		Metal		
Protection grade		IEC standard IP67		
Alternative model at home and abroad		LJ18A3-18-□□		