



INDUCTIVE PROXIMITY SWITCH				
Structural category		Plane installation type		
Outward appearance code		<b>LMF39</b>		
Appearance				
Dimension				
Flush	Detection distance			
	DC 6	NPN	NO	
			NC	
			NO+NC	
	~ 36	PNP	NO	
			NC	
			NO+NC	
	V	two wire system	NO	
			NC	
	AC 90 ~ 250 V	SRC Control label silicon	NO	
NC				
NO+NC				
Relay output				
Non-Flush	Detection distance		1-50mm	
	DC 6	NPN	NO	3050NA
			NC	3050NB
			NO+NC	3050NC
	~ 36	PNP	NO	3050PA
			NC	3050PB
			NO+NC	3050PC
	V	two wire system	NO	3050LA
			NC	3050LB
	AC 90 ~ 250 V	SRC Control label silicon	NO	2050A
			NC	2050B
			NO+NC	2050C
		Relay output	2050JC	
Control output	DC	200mA		
	SCR/Relay	300mA/2A/10A		
Output voltage dropDC/AC		DC≤1.5V /DC(Two wire system)≤5V/ AC≤TV		
Consumption current		DC≤1mA/ DC(Two wire system)≤13mA /AC≤2mA		
Standard detected object		120×120×1(A3 iron)		
Repeated precision		0.5		
DC/AC Response frequency		50Hz/10Hz		
Working environment temperature		-25℃~75℃		
Insulation resistance		50MΩ		
Shell material		ABS Resin * Glass fiber reinforced plastic		
Protection grade		IEC standard IP65		
Alternative model at home and abroad		TCA-2050□		