



INDUCTIVE PROXIMITY SWITCH				
Structural category		Angular column type		
Outward appearance code		LMF7		
Appearance				
Dimension				
Flush	Detection distance		10mm	
	DC 6 ~ 36 V	NPN	NO	3010NA
			NC	3010NB
			NO+NC	
	PNP	NO	3010PA	
		NC	3010PB	
		NO+NC		
	two wire system	NO	3010LA	
		NC	3010LB	
	AC 90 ~ 250 V	SRC Control label silicon	NO	2010A
			NC	2010B
			NO+NC	2010C
Relay output				
Non-Flush	Detection distance		15mm	
	DC 6 ~ 36 V	NPN	NO	3015NA
			NC	3015NB
			NO+NC	3015NC
	PNP	NO	3015PA	
		NC	3015PB	
		NO+NC	3015PC	
	two wire system	NO	3015LA	
		NC	3015LB	
	AC 90 ~ 250 V	SRC Control label silicon	NO	2015A
			NC	2015B
			NO+NC	2015C
Relay output				
Control output	DC		200mA	
	SCR/Relay		300mA	
Output voltage dropDC/AC		DC<3V AC<10V		
Consumption current		DC<15mA AC<10mA		
Standard detected object		35×35×1(A3 iron)		
Repeated precision		0.05		
DC/AC Response frequency		200Hz/25Hz		
Working environment temperature		-25℃~75℃		
Insulation resistance		50MΩ		
Shell material		ABS Resin		
Protection grade		IEC standard IP67		
Alternative model at home and abroad		TL-N10M□		